



## Declaration of Compliance

|                                           |                                                                                                                                                                                                            |
|-------------------------------------------|------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| <b>Business Operator</b>                  | Vikan A/S<br>Rævevej 1<br>DK-7800 Skive<br>(+45) 96 14 26 00                                                                                                                                               |
| <b>Product name</b>                       | Aluminum Handle w/Hose Nozzle, waterfed, Ø31 mm, 1565 mm, White                                                                                                                                            |
| <b>Item Number</b>                        | 29915                                                                                                                                                                                                      |
| <b>Plastic Material</b>                   | Polypropylene, 98 %                                                                                                                                                                                        |
| <b>Colour masterbatch</b>                 | White, 2 %                                                                                                                                                                                                 |
| <b>Aluminium</b>                          | Aluminium Alloy 5449A welded tubes                                                                                                                                                                         |
| <b>Brass</b>                              | Chromium-plated brass coupling                                                                                                                                                                             |
| <b>EU Compliance</b>                      |                                                                                                                                                                                                            |
| Regulation (EC) No 2023/2006              | The product is produced according to EU Commission Regulation no. 2023/2006 of 22. December 2006 on good manufacturing practices for materials and articles intended to come into contact with food (GMP). |
| <b>US FDA Compliance</b>                  |                                                                                                                                                                                                            |
|                                           | All raw materials in this product are in compliance with FDA (Food and Drug Administration in the USA) 21 CFR parts 170 to 199.                                                                            |
|                                           | The polypropylene complies with FDA 21 CFR 177.1520 "olefin polymers".                                                                                                                                     |
|                                           | The brass in this product is in compliance with FDA (Food and Drug Administration in the USA) Food Code 2017 to be used solely with water and not in direct contact with food.                             |
| <b>Non-food contact usage temperature</b> | Minimum temperature: -20 °C<br>Maximum temperature: 80 °C                                                                                                                                                  |

**General**

Equipment should be cleaned, disinfected and sterilised, as appropriate to its intended use, before use.

It is also important to clean, disinfect and sterilise equipment as appropriate after use, using the appropriate decontamination chemicals, concentrations, times and temperatures.

Appropriate equipment decontamination will minimise the risk of microbial growth and cross contamination and will maximise the efficiency and durability of the equipment.

Recommended sterilisation temperature (Autoclave): 121 °C

We will make the relevant background documentation available to the competent authorities, at their request.

Vikan A/S is registered with the Danish Veterinary and Food Administration (DVFA), and our mandatory Own Control System is subject to inspection by the DVFA.

**Date**

4/26/2025

**Made By**

Marta Sztuka  
Materials and Compliance Specialist