

Declaration of Compliance

Business Operator	Vikan A/S Rævevej 1 DK-7800 Skive (+45) 96 14 26 00
Product name on web	Ultra-Slim Cleaning Brush with Long Handle, 600 mm, Medium, Red
Item Number	41974
	
Plastic Material	Polypropylene, 98 %
Colour masterbatch	Red, 2 %
Foaming agent	Chemical foaming agent, 1 %
Bristles	Polybutylene terephthalate (PBT)
Stainless steel	The stainless steel staple is made from stainless steel Grade 1.4301 (AISI 304)
EU Compliance	
Regulation (EC) No 1935/2004	In accordance with EU Commission Regulation no. 1935/2004 article 3, 11(5), 15 and 17 the product is intended for food contact. The product is marked with the "glass & fork" symbol on the packaging or on the product itself through moulding. The stainless steel complies with the French national requirements regarding composition of stainless steel, as defined in "Arrêté du 13 janvier 1976 relatif aux matériaux et objets en acier inoxydable au contact des denrées alimentaires." the specification for stainless steel in the DGCCRF "Fiche MCDA n°1 (V02 - 01/04/2017) titled food contact suitability of metals and alloys". 
AP(89)1	All pigments in the masterbatch comply with resolution AP 89(1)
Regulation (EC) No 2023/2006	The product is produced according to EU Commission Regulation no. 2023/2006 of 22. December 2006 on good manufacturing practices for materials and articles intended to come into contact with food (GMP).



Regulation (EU) No 10/2011	The monomers and additives used in the manufacture of this product are listed in Annex I to Regulation (EU) No 10/2011 of the European Parliament and of the Council of 14 January 2011 on plastic materials and articles intended to come into contact with food, as amended. Monomers and/or additives with specific migration limit (SML) are used. The substances with a SML will not migrate in quantities that will exceed the SML, under the specified conditions of use. Upon request we will supply relevant information regarding these substances on a confidential basis. Vikan A/S does not use multi-layer materials or articles with a functional barrier.
Regulations (EC) No 1333/2008 and (EC) No 1334/2008	This material contains intentionally added "dual use" additives for which restrictions or purity criteria are in place in accordance with Regulations (EC) 1333/2008 and (EC) 1334/2008. Upon request we will supply relevant information regarding these substances on a confidential basis.
(EU) 2024/3190	The product has been manufactured and assessed in compliance with the criteria established by Regulation (EU) 2024/3190.
US FDA Compliance	All raw materials in this product are in compliance with FDA (Food and Drug Administration in the USA) 21 CFR parts 170 to 199. The polymers and additives complies with FDA 21 CFR part 174, 175, 176, 177, 178, 181, 182, 184, or 186. Additives are cleared according to FDA 21 CFR Part 178 (Indirect food additives), are generally recognised as safe (GRAS), are prior-sanctioned food ingredients, or are cleared on basis of regulations for food additives of before 1958. The polypropylene complies with FDA 21 CFR 177.1520 "olefin polymers". The PBT bristles comply with FDA 21 CFR 177.1660 „Poly(tetramethylene) terephthalate“. The pigments in the masterbatch are listed under FDA 21 CFR 178.3297 „Colorants for Polymers“. The stainless steel in this product is in compliance with FDA (Food and Drug Administration in the USA) Food Code 2017 and is listed in NSF/ANSI 51-2014 on Food Equipment Materials
UK Compliance	The product complies with The Materials and Articles in Contact with Food (Amendment) (EU Exit) Regulations 2019 No. 704
Danish Compliance	The product complies with the Danish consolidation Act no. 681 of 25/05/2020.
Japanese Compliance	All substances (polymers, monomers and additives) used in Vikan products comply with Article 18(3) of the Japanese Food Sanitation Act and are listed in Tables 1 and 2 of Appendix 1 of the Positive List.

Migration analysis plastics

Samples of the product, or a similar product made from identical plastic material, have been tested for overall migration according to the test conditions specified in (EU) 10/2011 for repeated use, and the article comply with the overall migration limit of 10 mg/dm² or 60 mg/kg.

Test conditions for overall migration were OM3 (2 h at 70 °C)

Food simulants used for overall migration were 10 % ethanol (simulant A), 3 % acetic acid (simulant B) and olive oil (simulant D2).

Compliance with specific migration limits, and other restrictions, has been documented through testing, calculation or simulation.

Test conditions for specific migration was 30 min at 80 °C

Max ratio of food contact surface area to volume 2.1 dm²/100 ml

Food contact types

The product is suitable for contact with the following types of food under the intended and foreseeable conditions of use:

- ☒ Aqueous
- ☒ Acidic
- ☒ Alcoholic
- ☒ Fatty
- ☒ Dry

Food contact usage time and temperature

Any food contact conditions up to 80 °C for 30 min

Non-food contact usage temperature

Minimum temperature: -20 °C
Maximum temperature: 100 °C

**General**

Equipment should be cleaned, disinfected and sterilised, as appropriate to its intended use, before use.

It is also important to clean, disinfect and sterilise equipment as appropriate after use, using the appropriate decontamination chemicals, concentrations, times and temperatures.

Appropriate equipment decontamination will minimise the risk of microbial growth and cross contamination and will maximise the efficiency and durability of the equipment.

Recommended sterilisation temperature (Autoclave): 121 °C

We will make the relevant background documentation available to the competent authorities, at their request.

Vikan A/S is registered with the Danish Veterinary and Food Administration (DVFA), and our mandatory Own Control System is subject to inspection by the DVFA.

The product is suitable for repeated use under the conditions specified in this Declaration of Compliance. Reuse does not affect the product's compliance with applicable food contact regulations, provided it remains intact, undamaged, and is cleaned appropriately between uses.

Date

1/14/2026

Made By

Marta Sztuka
Materials and Compliance Specialist