

# One-Piece Metal Detectable Shovel

10.2", Red



**Item Number: 6981MD4**

This one-piece polypropylene shovel is tough, lightweight, and hygienic. Molded from FDA-compliant polypropylene, it is a workhorse for moving bulk materials and an integral part of any professional cross-contamination containment, food safety or HACCP program. Initially developed over 30 years ago, our one-piece shovel doesn't just meet the standard, it sets the standard. The semi-ferrous additive in this shovel allows for use in conjunction with a metal detectable system. Metal detectable plastic is a lightweight and less costly alternative to stainless steel, and will reduce fatigue for the user. This shovel is popular for meat, dairy, seafood, and poultry processing, as well as commercial fishing and other food handling applications.

## General Information

<b>Color</b>	Red
<b>Material</b>	Polypropylene, Semi-Ferrous Additive
<b>Metal Detectable</b>	Yes
<b>Country of Origin</b>	United States

## Product Dimensions

<b>Product Length/Depth</b>	37.5 "
<b>Product Width</b>	10.2 "
<b>Product Height</b>	5.9 "
<b>Net Weight</b>	3.5273 lbs

## Packaging & Shipping Details

<b>Box Quantity</b>	6 Pcs.
<b>Quantity per Pallet (80 x 120 x approx.180 cm)</b>	0 Pcs.
<b>Quantity Per Layer (Pallet)</b>	0 Pcs.
<b>Box Length/Depth</b>	10 "
<b>Box Width</b>	43 "
<b>Box Height</b>	12 "
<b>Cardboard Packaging (Recycling symbol "20" PAP) per Pcs.</b>	0.44 lbs
<b>Total Tare Weight</b>	0.44 lbs
<b>Gross Weight</b>	3.9683 lbs
<b>Cubic Feet</b>	1.3083 ft3
<b>GTIN-13 Number</b>	812904022602
<b>Customs Tariff Number</b>	96039099

## Compliance & Standard Details



## Item Number: 6981MD4

Complies with FDA Regulation CFR 21 <sup>1</sup>	Yes
Complies with California Proposition 65	Yes
Complies with Halal and Kosher	Yes

## Technical Data

Handle Length	0 < 45,28 "
---------------	-------------

## Usage Limits

Recommended sterilisation temperature (Autoclave)	249.8 °F
Max. cleaning temperature (Dishwasher)	199.4 °F
Max usage temperature (food contact)	183.2 °F
Min. usage temperature	-22 °F
Max. drying temperature	266 °F