


Aluminum Handle

Ø1", 57.5", Red



Item Number: 29594

This handle with colour-coded grip can be used with any product in the Vikan range.

General Information

Color	Red
Material	Anodised Aluminium, Polypropylene
UNSPSC Code	47131609
Country of Origin ISO Code	DK
Country of Origin	Denmark

Product Dimensions

Handle Length	1301 - 1700 mm
Product Length/Depth	1460 mm
Product Width	25 mm
Product Height	25 mm
Net Weight	0.33 kg

Packaging & Shipping Details

Box Quantity	10 Pcs.
Quantity per Pallet (80 x 120 x approx.180 cm)	500 Pcs.
Quantity Per Layer (Pallet)	50 Pcs.
Box Length/Depth	1480 mm
Box Width	160 mm
Box Height	60 mm
Plastic Packaging (Recycling Symbol "4") per pcs.	0.0056 kg
Total Tare Weight	0.0056 kg
Gross Weight	0.34 kg
Cubic metre	0.000913 M3
GTIN-13 Number	5705020295942
GTIN-14 Number (Box quantity)	15705020295949
Customs Tariff Number	76169990

Compliance & Standard Details

Item Number: 29594

Complies with (EC) 1935/2004 on food contact materials ¹	Yes
Complies with EU Regulation 2023/2006/EC of Good Manufacturing Practice	Yes
Complies with FDA Regulation CFR 21 ¹	Yes
Complies with UK 2019 No. 704 on food contact materials	Yes
Meets the REACH Regulation (EC) No. 1907/2006	Yes
Complies with California Proposition 65	Yes
Complies with Halal and Kosher	Yes
PFAS intentionally added	No

Technical Data

Connection	Euro Threaded
Product Diameter	25 mm

Usage Limits

Recommended sterilisation temperature (Autoclave)	121 °F
Max. usage temperature (for food contact)	100 °C
Max usage temperature (non food contact)	100 °C
Min. usage temperature ³	-20 °C
Max. drying temperature	100 °C
Min. pH-value in usage concentration	2 pH
Max. pH-value in Usage Concentration	8 pH

Sustainability Details

Recycling Symbol "7", Miscellaneous Plastics	No
--	----

New equipment should be cleaned, disinfected, sterilized, and any labels removed, as appropriate to its intended use, e.g. high risk vs. low risk food production areas, general hospital areas vs. intensive care units, before use.

3. Do not store the product below 32 °Fahrenheit.