

70436

Deck Scrub, waterfed, 10.6", Medium, Yellow



This deck scrub has very effective water distribution and is ideal for use in heavily soiled areas such as slaughterhouses and meat processing plants.

Technical Data

Item Number	70436
Bristle stiffness	Medium
Visible bristle length	1.3 "
Connection	Threaded
Material	Polypropylene Polyester (PBT) Stainless Steel (AISI 304L)
Complies with (EC) 1935/2004 on food contact materials¹	Yes
Complies with EU Regulation 2023/2006/EC of Good Manufacturing Practice	Yes
Complies with FDA Regulation CFR 21¹	Yes
Complies with UK 2019 No. 704 on food contact materials	Yes
Meets the REACH Regulation (EC) No. 1907/2006	Yes
Complies with California Proposition 65	Yes
Complies with Halal and Kosher	Yes
PFAS intentionally added	No
Design Registration No.	EU 008554125-0005, UK 6139375
Box Quantity	10 Pcs.
Quantity per Pallet (80 x 120 x approx.180 cm)	800 Pcs.
Quantity Per Layer (Pallet)	80 Pcs.
Box Length/Depth	15 "
Box Width	11.4 "
Box Height	6.9 "
Product Length/Depth	10.6 "
Product Width	3 "
Product Height	3.9 "
Net Weight	0.9039 lbs
Plastic Packaging (Recycling Symbol "4") LDPE	0.02 lbs
Cardboard Packaging (Recycling symbol "20" PAP)	0.05 lbs
Total Tare Weight	0.07 lbs
Gross Weight	0.9716 lbs
Cubic Feet	0.0716 ft ³
Recommended sterilisation temperature (Autoclave)	249.8 °F
Max. cleaning temperature (Dishwasher)	199.4 °F
Max usage temperature (food contact)	176 °F
Max usage temperature (non food contact)	212 °F
Min. usage temperature	-4 °F

Max. drying temperature	212 °F
Min. pH-value in usage concentration	2 pH
Max. pH-value in Usage Concentration	10.5 pH
GTIN-13 Number	5705020704369
GTIN-14 Number (Box quantity)	15705020704366
Customs Tariff Number	96039099
UNSPSC Code	47131605
Country of Origin ISO Code	DK
Country of Origin	Denmark

New equipment should be cleaned, disinfected, sterilized, and any labels removed, as appropriate to its intended use, e.g. high risk vs. low risk food production areas, general hospital areas vs. intensive care units, before use.

3. Do not store the product below 32 °Fahrenheit.