

UST Deck Scrub

15.7", Stiff, Green



Item Number: 70642



This ULTRA SAFE TECHNOLOGY (UST) Deck Scrub comes with angled Filament Security Units for effective removal of stubborn dirt from both textured and smooth surfaces in high-risk areas. All UST brushes feature a unique bristle system that minimises the risk of contamination and bristle loss.

General Information

Bristle stiffness	Stiff
Connection	Euro Threaded
Color	Green
Material	Polyester (PBT), Glass reinforced, Polypropylene
UNSPSC Code	47131605
Country of Origin	Denmark

Product Dimensions

Visible bristle length	1.5 "
Product Length/Depth	15.7 "
Product Width	2 "
Product Height	3 "
Net Weight	0.7716 lbs

Packaging & Shipping Details

Box Quantity	10 Pcs.
Quantity per Pallet (80 x 120 x approx.180 cm)	400 Pcs.
Quantity Per Layer (Pallet)	50 Pcs.
Box Length/Depth	16.1 "
Box Width	11.4 "
Box Height	7.9 "
Plastic Packaging (Recycling Symbol "4") LDPE per Pcs.	0.01 lbs
Cardboard Packaging (Recycling symbol "20" PAP) per Pcs.	0.05 lbs
Total Tare Weight	0.07 lbs
Gross Weight	0.8377 lbs
Cubic Feet	0.053 ft3
GTIN-13 Number	5705020706424
GTIN-14 Number (Box quantity)	15705020706421
Customs Tariff Number	96039099



Item Number: 70642

Compliance & Standard Details

Complies with (EC) 1935/2004 on food contact materials ¹	Yes
Complies with EU Regulation 2023/2006/EC of Good Manufacturing Practice	Yes
Complies with FDA Regulation CFR 21 ¹	Yes
Complies with UK 2019 No. 704 on food contact materials	Yes
Meets the REACH Regulation (EC) No. 1907/2006	Yes
Complies with California Proposition 65	Yes
Complies with Halal and Kosher	Yes
PFAS intentionally added	No

Usage Limits

Max usage temperature (food contact)	176 °F
Max usage temperature (non food contact)	176 °F
Recommended sterilisation temperature (Autoclave)	249.8 °F
Max. cleaning temperature (Dishwasher)	199.4 °F
Max. drying temperature	212 °F
Min. usage temperature	-4 °F
Max. pH-value in Usage Concentration	10.5 pH
Min. pH-value in usage concentration	2 pH

Design & Patent Registration Details

Design Registration No.	EU 002189654-0001, EU 002650838-1-4, US D793091, EU 002650580-1-7, GB 9002650830001-4, G 900265505800001-7
Pat. Pending/Patent No.	EP2816930 validated in DE, FR, GB and DK. US9204712 EP2816929 validated in DE, FR, GB and DK. US9357831

Sustainability Details

Recycling Symbol "7", Miscellaneous Plastics	Yes
--	-----

New equipment should be cleaned, disinfected, sterilized, and any labels removed, as appropriate to its intended use, e.g. high risk vs. low risk food production areas, general hospital areas vs. intensive care units, before use.

1. See Declaration of Compliance for further details on food contact

3. Do not store the product below 32 °Fahrenheit.

