

77646

# Revolving Neck Floor squeegee w/Replacement Cassette, 23.6", Yellow



Ideal for removing water and food debris from all types of flooring, this double-bladed cell rubber squeegee can be used with any Vikan handle. The cassette can be removed easily for cleaning or replacement (Series 77745 or 77749 for replacement blades).

# Technical Data

Item Number	77646
Connection	Threaded
Material	Polypropylene Cellular rubber
Complies with (EC) 1935/2004 on food contact materials <sup>1</sup>	No
Complies with FDA Regulation CFR 21 <sup>1</sup>	No
Complies with UK 2019 No. 704 on food contact materials	No
Meets the REACH Regulation (EC) No. 1907/2006	Yes
Complies with California Proposition 65	No
Complies with Halal and Kosher	Yes
PFAS intentionally added	No
Pat. Pending/Patent No.	EP2227129 validated in DK, DE, FR and GB. DE 602008048400.9
Box Quantity	10 Pcs.
Quantity per Pallet (80 x 120 x approx.180 cm)	280 Pcs.
Quantity Per Layer (Pallet)	40 Pcs.
Box Length/Depth	24 "
Box Width	11.4 "
Box Height	7.9 "
Product Length/Depth	23.6 "
Product Width	3.9 "
Product Height	3 "
Net Weight	0.8377 lbs
Weight bag (Recycling Symbol "4") LDPE	0.02 lbs
Weight cardboard (Recycling symbol "20" PAP)	0.07 lbs
Total Tare Weight	0.09 lbs
Gross Weight	0.927 lbs
Cubic Feet	0.159 ft <sup>3</sup>
Max. cleaning temperature (Dishwasher)	194 °F
Max usage temperature (food contact)	176 °F
Max usage temperature (non food contact)	176 °F
Min. usage temperature	-4 °F
Max. drying temperature	158 °F
Min. pH-value in usage concentration	2 pH
Max. pH-value in Usage Concentration	10.5 pH
GTIN-13 Number	5705020776465
GTIN-14 Number (Box quantity)	15705020776462

<b>Customs Tariff Number</b>	96039099
<b>UNSPSC Code</b>	47121812
<b>Country of Origin ISO Code</b>	DK
<b>Country of Origin</b>	Denmark

New equipment should be cleaned, disinfected, sterilized, and any labels removed, as appropriate to its intended use, e.g. high risk vs. low risk food production areas, general hospital areas vs. intensive care units, before use.

3. Do not store the product below 32 °Fahrenheit.