

Coupling with Hose Nozzle and Shut-Off Valve

1/2" (Q)



Item Number: 880703



1/2" coupling "Q" with 1/2" hose nozzle and shut-off valve when the hose is disconnected. Hose clamp is included. Low lead content.

General Information

Material	Chromium-plated brass, Galvanized steel (DIN 1.09035)
Country of Origin	Denmark

Product Dimensions

Product Length/Depth	73 mm
Product Width	28 mm
Product Height	28 mm
Net Weight	0.157 kg

Packaging & Shipping Details

Box Quantity	10 Pcs.
Quantity per Pallet (80 x 120 x approx.180 cm)	4800 Pcs.
Quantity Per Layer (Pallet)	240 Pcs.
Box Length/Depth	240 mm
Box Width	150 mm
Box Height	75 mm
Plastic Packaging (Recycling Symbol "4") LDPE per Pcs.	0.0015 kg
Cardboard Packaging (Recycling symbol "20" PAP) per Pcs.	0.009 kg
Total Tare Weight	0.0105 kg
Gross Weight	0.17 kg
Cubic metre	5.7E-05 M3
GTIN-13 Number	5705022046658
GTIN-14 Number (Box quantity)	15705028046666
Customs Tariff Number	74122000

Compliance & Standard Details

Complies with FDA Regulation CFR 21 ¹	Yes
--	-----

Item Number: 880703

Complies with REACH Regulation (EC) No. 1907/2006	Yes
Complies with California Proposition 65	Yes
Complies with Halal and Kosher	Yes
PFAS intentionally added	No

Technical Data

Couplings Size	1/2 "
----------------	-------

Usage Limits

Max. cleaning temperature (Dishwasher)	80 °C
Max usage temperature (non food contact)	70 °C
Min. usage temperature ³	-30 °C
Min. pH-value in usage concentration	2 pH
Max. pH-value in Usage Concentration	11 pH
Max. bars pressure	25 Bar

The hose coupling on the hose and foaming gun have to be greased regularly to maintain the coupling ability on the equipment. The grease applied during mounting will be rinsed away by the water flow and thus needs to be renewed.
1. The product is suitable for use with water only and not for direct food contact.

