

9472

Dilution unit for several products, 1/2"



Accurately dose chemicals ranging from 0.2% to 9% in bottles, small buckets and floor cleaning machines. Allows for optimal cleaning and chemical savings. The dosing unit is approved with a reflux protection device. It can be mounted on the wall or directly on the water tap. Connect with 1/2" clutch housing.

Technical Data

Item Number	9472
Couplings Size	1/2 "
Approval	VA 3.14/18252
Material	POM Chromium-plated brass
FDA compliant raw material (CFR 21)	No
Meets the REACH Regulation (EC) No. 1907/2006	Yes **
Box Quantity	1 Pcs.
Quantity per Pallet (80 x 120 x 200 cm)	420 Pcs
Quantity Per Layer (Pallet)	1 Pcs.
Box Length	285 mm
Box Width	250 mm
Box Height	85 mm
Length	280 mm
Width	250 mm
Height	85 mm
Gross Weight	1,19 kg
Net Weight	1,05 kg
Cubik metre	0,0061 M3
Max usage temperature (non food contact)	60 °C
Min. usage temperature³	5 °C
Min. pH-value in usage concentration	2 pH
Max. pH-value in Usage Concentration	11 pH
Min. Bars pressure	2 Bar
Max. bars pressure	10 Bar
Gtin-13 Number	5705020094729
GTIN-14 Number (Box quantity)	15705020094726
Customs Tariff No.	84818099
Country of origin	Denmark

* The dosing unit has to be flushed with an acidic detergent minimum once per week to ensure optimum use – (pH 2-1).

- The hose coupling on the inlet hose and MiniMix must be greased frequently to maintain the coupling ability. The grease applied during mounting will be flushed away and thus need to be re-newed.
- We recommend you to replace the nozzles frequently to avoid any clogging.

** Lead (Pb, CAS: 7439-92-1) is on the REACH candidate list as a Substance of Very High Concern (SVHC). This product contains lead (Pb) in a concentration above 0.1% w/w. Consequently the REACH Regulation (EC) No. 1907/2006 require Vikan to notify our customers of the content of lead.